



# Lexmark CS331dw

**Small. Dependable. Secure.**

Enhance small-workgroup productivity with colour output up to 24 pages per minute\*, high-yield replacement toner cartridges and connectivity via Wi-Fi, USB and gigabit ethernet—all in the Lexmark CS331dw. Its 1-GHz multi-core processor lets you tackle big jobs, while Lexmark full-spectrum security helps protect your data.



## Compact colour power

- ▶ Get colour output at up to 24 pages per minute\*.
- ▶ Tackle your printing workload with the power of a 1-GHz processor and 512 MB of memory.
- ▶ Connect via standard Wi-Fi, gigabit ethernet and USB.
- ▶ Simplify mobile printing via Lexmark Mobile Print app, as well as Mopria® and AirPrint technologies.
- ▶ Two-line display lets you configure, interact and monitor vital system information.

## Easy to set up, easy to keep going

- ▶ Compact dimensions of 243.7 mm high x 411.2 mm wide x 394.1 mm deep helps it fit almost anywhere.
- ▶ Unison™ Toner replacement cartridges deliver up to 4500 pages\*\* of high-quality output.

- ▶ Steel frame and lifetime imaging components mean long life and minimal maintenance.

## Robust, built-in security

- ▶ Lexmark's full-spectrum security architecture helps keep your information safe—on the document, the device, over the network, and everywhere in between.

## Built for planet earth

- ▶ Built-in energy-saving mode goes from sleep to print to sleep with nothing to set.
- ▶ Printer is rated EPEAT® Silver\*\*\* and is ENERGY STAR® certified.
- ▶ Recycle cartridges through the award-winning Lexmark Cartridge Collection Programme (LCCP).



\* Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

\*\* Average continuous black or continuous composite colour (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See [www.lexmark.com/yields](http://www.lexmark.com/yields) for more information.

\*\*\* EPEAT ratings may vary by location. See [www.epeat.net](http://www.epeat.net) for registration status by country.

## Product Specifications

## Lexmark CS331dw

### Printing

Display	2-line (APA) monochrome LCD display
Print speed	up to: black: 24 ppm <sup>1</sup> (A4) / colour: 24 ppm <sup>1</sup> (A4)
Time to first page	as fast as: black: 10.9 seconds / colour: 10.9 seconds
Print resolution	black: 4800 CQ (2400 x 600 dpi) / colour: 4800 CQ (2400 x 600 dpi)
Memory	standard: 512 MB / maximum: 512 MB
Hard Disk	Not available
Recommended monthly page volume	600 - 2500 pages <sup>2</sup>
Maximum monthly duty cycle	up to: 50000 pages per month <sup>3</sup>

### Supplies<sup>4</sup>

Cartridge yields	up to: 4,500 <sup>5</sup> -page Black High Yield Cartridge / up to: 4,500 <sup>5</sup> -page Colour (CMY) High Yield Cartridges / up to: 1500 <sup>5</sup> -page black and colour (CMY) cartridges
Cartridge(s) shipped with product	750 <sup>5</sup> -page Black Return Program Toner Cartridge <sup>5</sup> , 500 <sup>5</sup> -page Colour (CMY) Return Program Toner Cartridge <sup>5</sup>

### Paper Handling

Standard paper handling	100-Sheet Output Bin, Integrated Duplex, Single-sheet manual feed, 250-sheet input
Paper input capacity	up to: standard: 250+1 pages / maximum: 250+1 pages
Paper output capacity	up to: standard: 100 pages / maximum: 100 pages
Media types supported	Paper Labels, Card Stock, Plain Paper, Envelopes, Glossy paper, Refer to the Paper & Specialty Media Guide
Media sizes supported	A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Hagaki card, Letter, B5 Envelope, Statement, C5 Envelope, Executive, Universal, DL Envelope, Folio, 10 Envelope

### General Information<sup>6</sup>

Standard connectivity	802.11b/g/n Wireless, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000; RJ-45)
Noise Level	Operating: 52 dBA (Print)
Specified operating environment	Humidity: 8 to 80% Relative Humidity / Altitude: 0 - 3048 meters / Temperature: 10 to 32°C (50 to 90°F)
Product guarantee	1-Onsite Repair, 3 -5 Business Days
Size / Weight	HxWxD: 243.7 x 411.2 x 394.1 mm / 16.1 kg
Energy Star Typical Electricity Consumption	TEC: 0.31 kWh per week

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

<sup>1</sup> Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

<sup>2</sup> "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. <sup>3</sup> "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. <sup>4</sup> Product functions only with replacement cartridges designed for use in a specific geographical region. See [www.lexmark.com/regions](http://www.lexmark.com/regions) for more details. <sup>5</sup> Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798. <sup>6</sup> Printers are sold subject to certain license/agreement conditions. See [www.lexmark.com/printerlicense](http://www.lexmark.com/printerlicense) for details.

© 2019 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. AirPrint and the AirPrint Logo are trademarks of Apple, Inc. Google Cloud Print™ is a trademark of Google, LLC. Mopria®, the Mopria® Logo™ and the Mopria® Alliance logos are registered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorised use is strictly prohibited. All other trademarks are the property of their respective owners. This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).