



 Lexmark™

Lexmark CX635adwe

Exceptional performance, secure and sustainable



Lexmark CX635adwe

With exceptional performance and secure design, the CX635adwe Multifunction printer (copy/scan/print/fax) delivers enhanced productivity up to 40 ppm* on A4 paper and toner yields up to 20,000 pages mono**, and up to 11,700 pages colour**. Engineered for long life with environmental certifications and advanced power management, this efficient model has high sustainability. Fast time to first print, superior print quality and easy-to-use touch screen.

Secure by design

Lexmark expertise helps customers protect their data, their device and their network. Our security ecosystem is designed to overcome the most complex data challenges. And now we've added the Trusted Platform Module (TPM)***, which includes on-board authentication, system integrity checks, and cryptographic capabilities to create a unique digital system fingerprint. TPM meets stringent industry and US government security standards including Common Criteria and Federal Information Processing Standard (FIPS).

Proprietary technology

We own core technology across hardware, firmware, services, and solutions, creating seamless connections designed to reduce the risk of security gaps between your document, your device and your network. Our expertise is our customer's benefit.

Sustainability

With certifications in Energy Star®, Blue Angel, RoHS, EPEAT® Silver. Models are sustainable for today and beyond. Lexmark is an industry leader of recycled content with products using at least 35% PCR content and continual focus on improvement. This line is also engineered for Long Life and designed to last and reduce waste.

Intelligent Design

Every touch point is designed to withstand high usage while meeting accessibility standards. Steel frames support the device and provide durability to help ensure consistent long-

term performance. Products are designed for long service life with long-life components and are easily serviced with few tools.



Optimised productivity

Increase productivity with optimised performance. Print at up to 40 pages per minute* (A4) and capture information quickly with scan speeds of up to 49 images per minute (A4) for one-sided scanning, and up to 98 images per minute (A4) for two-sided scanning.

Manageability

These IoT-ready devices can be remotely managed, including setup, configuration, consumables management, and diagnostics. Wireless capability gives freedom of access and remote firmware updates make it easy to upgrade to the latest apps and security features. Our mobile printing app makes it easier to monitor and manage your print jobs from remote locations, all from the touch of your phone.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

* Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: www.lexmark.com/ISOspeeds.

** Average continuous black or continuous composite colour (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See www.lexmark.com/yields for more information. In demonstration of circular economy principles, genuine Lexmark supplies with Unison™ Toner may contain components recovered from the Lexmark Cartridge Collection Programme (LCCP).

*** The Trusted Platform Module (TPM) is not available in some countries.

Lexmark CX635adwe



- 1 **Multifunction product with 17.8 cm touch screen**
491.4 x 479 x 475.1 mm
- 2 **200-Sheet output bin**
Dimensions included as part of base model
- 3 **Single sheet multipurpose feeder**
Dimensions included as part of base model
- 4 **250-Sheet tray**
Dimensions included as part of base model
- 5 **650-Sheet Duo Tray**
132.1 x 424.2 x 416.6 mm
- 6 **550-Sheet Tray**
132.1 x 424.2 x 416.6 mm

- 7 **550-Sheet Tray**
132.1 x 424.2 x 416.6 mm
- 8 **Printer Stand (adjustable height)**
521 x 653 x 625 mm
- 9 **Swivel cabinet (25 cm, incl. storage)**
263 x 476 x 600 mm
- 10 **Convenience Stapler HV**
82 x 109 x 121 mm



P/N 50M7090 **Hardware** Lexmark CX635adwe

| | |
|------------|---|
| P/N | Supplies |
| 35S8500 | Staple Cartridges |
| 75M0W00 | Lexmark CS531, 632, 639, CX532, 635, C2335, XC2335 30K Waste Toner Bottle |
| 75M0X10 | Lexmark CS632, CX635 Black 20K Toner Cartridge |
| 75M0X20 | Lexmark CS632, CX635 Cyan 11.7K Toner Cartridge |
| 75M0X30 | Lexmark CS632, CX635 Magenta 11.7K Toner Cartridge |
| 75M0X40 | Lexmark CS632, CX635 Yellow 11.7K Toner Cartridge |
| 75M0Z10 | Lexmark CS531, 632, 639, CX532, 635 Black 150K Imaging Kit |
| 75M0Z50 | Lexmark CS531, 632, 639, CX532, 635 4-Colour 150K Imaging Kit |
| 75M0ZK0 | Lexmark CS531, 632, 639, CX532, 635, C2335, XC2335 Black Return Programme 150K Imaging Kit |
| 75M0ZV0 | Lexmark CS531, 632, 639, CX532, 635, C2335, XC2335 4-Colour Return Programme 150K Imaging Kit |
| 75M20C0 | Lexmark CS531, 632, CX532, 635 Cyan Return Programme 2K Toner Cartridge |
| 75M20K0 | Lexmark CS531, 632, CX532, 635 Black Return Programme 3K Toner Cartridge |
| 75M20M0 | Lexmark CS531, 632, CX532, 635 Magenta Return Programme 2K Toner Cartridge |
| 75M20Y0 | Lexmark CS531, 632, CX532, 635 Yellow Return Programme 2K Toner Cartridge |
| 75M2XC0 | Lexmark CS632, CX635 Cyan Return Programme 11.7K Toner Cartridge |
| 75M2XK0 | Lexmark CS632, CX635 Black Return Programme 20K Toner Cartridge |
| 75M2XM0 | Lexmark CS632, CX635 Magenta Return Programme 11.7K Toner Cartridge |
| 75M2XY0 | Lexmark CS632, CX635 Yellow Return Programme 11.7K Toner Cartridge |
| P/N | Paper Handling |
| 47C4590 | Convenience Stapler |
| 50M7550 | 550-Sheet Tray |
| 50M7650 | 650-Sheet Duo Tray |
| P/N | Memory Options |
| 27X0805 | 500+ GB Hard Disk |
| 57X9528 | Intelligent Storage Drive (ISD) |
| P/N | Application Solutions |
| 57X0300 | Contact Authentication Device |
| 57X0301 | Contactless Authentication Device |
| 82S1203 | IPDS License |
| 82S1204 | Bar Code License |
| P/N | Connectivity |
| 1021294 | USB Cable (2 meter) |
| 57X7040 | English Keyboard Kit |
| SPD0002 | Surge protective device |
| P/N | Furniture |
| 3073173 | Swivel cabinet (25 cm, incl. storage) |
| 40C2300 | CS72x, CX725 Printer Stand (adjustable height) |

Product Specifications

Lexmark CX635adwe

| Printing | |
|---|--|
| Display | Lexmark e-Task 7-inch (17.8 cm) colour touch screen |
| Print speed | up to: black: 40 ppm ¹ (A4) / colour: 40 ppm ¹ (A4) |
| Time to first page | as fast as: black: 6.3 seconds / colour: 6.3 seconds |
| Print resolution | black: 1200 x 1200 dpi, 4800 Color Quality / colour: 4800 Color Quality, 1200 x 1200 dpi |
| Memory | standard: 2048 MB / maximum: 2048 MB |
| Hard Disk | Intelligent Storage Drive available; Magnetic Hard Disk available |
| Recommended monthly page volume | 1,500 - 10,000 pages ² |
| Maximum monthly duty cycle | up to: 125,000 pages per month ³ |
| Copying | |
| Copy speed | up to: black: 39.5 cpm ¹ (A4) / colour: 39.5 cpm ¹ (A4) |
| Time to first copy | as fast as: black: 6.7 seconds / colour: 6.6 seconds |
| Scanning | |
| ADF scan | DADF (single pass Duplex) |
| Duplex scan speed | up to: black: 98 / 104 spm (A4) / colour: 80 / 84 spm (A4) |
| Simplex scan speed | up to: black: 49 / 52 spm (A4) / colour: 40 / 42 spm (A4) |
| ADF paper input capacity | up to: 100 pages |
| Faxing | |
| Modem speed | ITU T.30, V.34 Half-Duplex, 33.6 kbps |
| Supplies ⁴ | |
| Cartridge yields | up to: 20,000 ⁵ -page black cartridge / up to: 11,700 ⁵ -page Colour (CMY) Cartridges |
| Cartridge(s) shipped with product | 3000 ⁵ -page black starter Return Programme toner cartridge ⁵ , 2000 ⁵ -page colour (CMY) Return Programme toner cartridges ⁵ |
| Paper Handling | |
| Standard paper handling | 200-Sheet Output Bin, Integrated Duplex, Single sheet multipurpose feeder, 250-Sheet Tray |
| Optional paper handling | 650-Sheet Duo Tray, 550-Sheet Tray |
| Paper input capacity | up to: standard: 251 pages / maximum: 2001 pages |
| Paper output capacity | up to: standard: 200 pages / maximum: 200 pages |
| Media types supported | Vinyl Labels, Paper Labels, Card Stock, Plain Paper, Envelopes, Refer to the Paper & Specialty Media Guide |
| Media sizes supported | A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Hagaki card, Letter, B5 Envelope, Statement, C5 Envelope, Executive, Universal, DL Envelope, Folio, 10 Envelope |
| General Information ⁶ | |
| Standard connectivity | Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear USB 2.0 Hi-Speed certified port (type A), 802.11a/b/g/n/ac + Apple iBeacon, USB 2.0 Specification Hi-Speed Certified (Type B) |
| Noise Level | Operating: 53 dBA (Print) / 52 dBA (Copy) / 44 dBA (Scan) |
| Specified operating environment | Altitude: 0 - 2900 Metres (9,500 Feet) / Humidity: 15 to 80% Relative Humidity / Temperature: 10 to 32.2°C (50 to 90°F) |
| Product guarantee | 1-Year Onsite Service, Next Business Day |
| Size / Weight | HxWxD: 491.4 x 479 x 475.1 mm / 27.05 kg |
| Energy Star Typical Electricity Consumption | TEC: 0.57 kWh per week |

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹ Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

² "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³ "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴ Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. ⁵ Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798. ⁶ Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

© 2023 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are registered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorised use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT® is a trademark of the Green Electronics Council in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).