

Lexmark MC3224adwe

Small. Dependable. Secure.

Compact and lightweight, the Lexmark MC3224adwe multifunction brings colour printing, scanning, copying, faxing and touch-screen convenience to small workgroups. It offers colour output at up to 22 pages per minute* in a package that fits almost anywhere. There's Wi-Fi to support mobile users and Lexmark full-spectrum security is built in.



Compact colour versatility

- ▶ Get colour output at up to 22 pages per minute*, plus automatic-feed single-side scanning and analogue faxing.
- ▶ Tackle your printing workload with the power of a 1-GHz processor and 512 MB of memory.
- ▶ Connect via standard Wi-Fi, ethernet and USB.
- ▶ Simplify mobile printing via Lexmark Mobile Print app, as well as Mopria® and AirPrint technologies.
- ▶ 7.2 cm touch screen offers built-in workflow capabilities like scan to network, scan to e-mail and Lexmark's own Cloud Connector****.

Easy to set up, easy to keep going

- ▶ Compact dimensions of 344.4 mm high x 411.2 mm wide x 394.1 mm deep helps it fit almost anywhere.
- ▶ Unison™ Toner replacement cartridges deliver up to 1500 pages** of high-quality output.

- ▶ Steel frame and lifetime imaging components mean long life and minimal maintenance.

Robust, built-in security

- ▶ Lexmark's full-spectrum security architecture helps keep your information safe—on the document, the device, over the network, and everywhere in between.

Built for planet earth

- ▶ Built-in energy-saving mode goes from sleep to print to sleep with nothing to set.
- ▶ Printer is rated EPEAT® Silver*** and is ENERGY STAR® certified.
- ▶ Recycle cartridges through the award-winning Lexmark Cartridge Collection Programme (LCCP).



* Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

** Average continuous black or continuous composite colour (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See www.lexmark.com/yields for more information.

*** EPEAT ratings may vary by location See www.epeat.net for registration status by country

**** Cloud Connector feature is available by end of 2019. Devices purchased prior to availability can get this feature via free firmware update at support.lexmark.com/firmware.

Product Specifications

Lexmark MC3224adwe

Printing	
Display	2.8 inch (7.2 cm) LCD touch panel
Print speed	up to: black: 22 ppm ¹ (A4) / colour: 22 ppm ¹ (A4)
Time to first page	as fast as: black: 11 seconds / colour: 11 seconds
Print resolution	black: 4800 CQ (2400 x 600 dpi), 600 x 600 dpi / colour: 4800 CQ (2400 x 600 dpi), Up to 600 x 600 dpi
Memory	standard: 512 MB / maximum: 512 MB
Hard Disk	Not available
Recommended monthly page volume	250 - 2000 pages ²
Maximum monthly duty cycle	up to: 40000 pages per month ³
Copying	
Copy speed	up to: black: 22.8 cpm ¹ (A4) / colour: 22.8 cpm ¹ (A4)
Time to first copy	as fast as: black: 13.4 seconds / colour: 13.4 seconds
Scanning	
Scanner type / ADF scan	Flatbed scanner with ADF / Simplex
Simplex scan speed	up to: black: 20 / 21 spm (A4) / colour: 20 / 21 spm (A4)
ADF paper input capacity	up to: 50 pages
Faxing	
Modem speed	Max is 33,600 bps, V.34 Half-Duplex kbps
Supplies ⁴	
Cartridge yields	up to: 1500 ⁵ -page black and colour (CMY) cartridges
Cartridge(s) shipped with product	750 ⁵ -page Black Return Program Toner Cartridge, 500 ⁵ -page Colour (CMY) Return Program Toner Cartridge
Paper Handling	
Standard paper handling	100-Sheet Output Bin, Integrated Duplex, Single-sheet manual feed, 250-sheet input
Paper input capacity	up to: standard: 250+1 pages / maximum: 250+1 pages
Paper output capacity	up to: standard: 100 pages / maximum: 100 pages
Media types supported	Hagaki card, Paper Labels, Card Stock, Plain Paper, Glossy paper, Refer to the Paper & Specialty Media Guide
Media sizes supported	A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Hagaki card, Letter, B5 Envelope, Statement, C5 Envelope, Executive, Universal, DL Envelope, Folio, 10 Envelope
General Information ⁶	
Standard connectivity	Front Hi-Speed USB port (compatible with USB 2.0 specification, type A), 802.11b/g/n Wireless, USB 2.0 Specification Hi-Speed Certified (Type B), Fast Ethernet (RJ-45)
Noise Level	Operating: 49 dBA (Print) / 49 dBA (Copy) / 44 dBA (Scan)
Specified operating environment	Humidity: 8 to 80% Relative Humidity / Altitude: 0 - 3048 meters / Temperature: 10 to 32°C (50 to 90°F)
Product guarantee	1-Onsite Repair, 3 -5 Business Days
Size / Weight	HxWxD: 344.4 x 411.2 x 394.1 mm / 19.4 kg
Energy Star Typical Electricity Consumption	TEC: 0.34 kWh per week

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹ Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

² "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³ "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴ Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. ⁵ Average continuous cartridge yield is stated number of standard pages as listed. Declared yield value in accordance with ISO/IEC 19798. ⁶ Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details.

© 2019 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. AirPrint and the AirPrint Logo are trademarks of Apple, Inc. Google Cloud Print™ is a trademark of Google, LLC. Mopria®, the Mopria® Logo™ and the Mopria® Alliance logos are registered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorised use is strictly prohibited. All other trademarks are the property of their respective owners. This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).