



Lexmark CX331adwe

Malen. Pouzdan. Sigurno.

Kompaktan i lagan, višefunkcijski Lexmark CX331adwe pruža ispis u boji, skeniranje, kopiranje, faksiranje i praktičnost zaslona osjetljivog na dodir za male radne skupine. Pruža ispis u boji do 24 stranice po minuti* u paketu koji pristaje gotovo svugdje. Bežična veza podržava mobilne korisnike, a Lexmarkov puni spektar sigurnosti je ugrađen.



Kompaktnost i svestranost u boji

- ▶ Ostvarite ispis u boji do 24 stranice po minuti*, kao i skeniranje pojedinačnih listova uz automatsko uvlačenje i analogno faksiranje.
- ▶ Izađite na kraj s radnim opterećenjem ispisa uz procesor snage 1 GHz i 512 MB memorije.
- ▶ Povežite standardnom bežičnom mrežom, Ethernetom i USB-om.
- ▶ Pojednostavnite mobilni ispis uz Lexmarkovu aplikaciju za mobilni ispis, kao i tehnologije Mopria® i AirPrint.
- ▶ Mogućnosti e-Task zaslona od 7,2 cm osjetljivog na dodir uključuju ugrađene mogućnosti radnog procesa poput skeniranja na mrežu, skeniranja na e-poštu te Lexmarkovog vlastitog rješenja Cloud Connector**** za povezivanje na oblak.

Jednostavno za postavljanje, jednostavno za održavanje

- ▶ Kompaktne dimenzije od 344,4 mm visine x 411,2 mm širine x 394,1 mm dubine omogućavaju postavljanje bilo gdje.

- ▶ Unison™ Toner zamjenski spremnici pružaju do 4500 stranica** ispisa visoke kvalitete.
- ▶ Čelični okvir i dugotrajne slikovne komponente znače dugovječnost uz minimalno održavanje.

Robusna, ugrađena sigurnost

- ▶ Lexmarkova arhitektura s punim spektrom sigurnosti pomaže vam u očuvanju sigurnosti informacija - u dokumentu, na uređaju, na mreži i na svim međutočkama.

Stvoreno za planet Zemlju

- ▶ Ugrađeni način uštede energije koji se iz stanja mirovanja budi i vraća u mirovanje bez ikakvog postavljanja.
- ▶ Pisač posjeduje rejting EPEAT® Silver*** te certifikat ENERGY STAR®.
- ▶ Reciklirajte spremnike putem nagrađivanog Programa prikupljanja spremnika tvrtke Lexmark (LCCP).



* Brzine ispisa i kopiranja mjerene u skladu s ISO/IEC 24734, odnosno ISO/IEC 24735 (ESAT). Za više informacija posjetite: www.lexmark.com/ISOspeeds.

** Prosječni deklarirani kapacitet spremnika za neprekinuti crno-bijeli ili neprekinuti kompozitni ispis u boji (CMY) u jednostranom (simplex) načinu rada do navedenog broja standardnih stranica u skladu s ISO/IEC 19798. Stvarni kapacitet znatno odstupa u ovisnosti o brojnim čimbenicima. Posjetite www.lexmark.com/yields za više informacija.

*** EPEAT rejting može odstupati ovisno o lokaciji. Posjetite www.epeat.net za status registracije po zemljama.

**** Značajka Cloud Connector bit će dostupna do kraja 2019. Uređaji kupljeni prije dostupnosti značajke mogu dobiti ovu značajku putem besplatnog ažuriranja firmvera na support.lexmark.com/firmware.

Product Specifications

Lexmark CX331adwe

Printing	
Display	2.8 inch (7.2 cm) LCD touch panel
Print Speed	Up to: Black: 24 ppm ¹ (A4) / Colour: 24 ppm ¹ (A4)
Time to First Page	As fast as: Black: 10.6 seconds / Colour: 10.6 seconds
Print Resolution	Black: 4800 CQ (2400 x 600 dpi) / Colour: 4800 CQ (2400 x 600 dpi)
Memory	Standard: 512 MB / Maximum: 512 MB
Hard Disk	Not Available
Recommended Monthly Page Volume	600 - 2500 pages ²
Maximum Monthly Duty Cycle	Up to: 50000 pages per month ³
Copying	
Copy Speed	Up to: Black: 24.7 cpm ¹ (A4) / Colour: 24.7 cpm ¹ (A4)
Time to First Copy	as fast as: Black: 13.1 seconds / Colour: 13.1 seconds
Scanning	
Scanner Type / ADF Scan	Flatbed scanner with ADF / Simplex
A4/Ltr Simplex Scan Speed	Up to: Black: 20 / 21 sides per minute / Colour: 20 / 21 sides per minute
ADF Paper Input Capacity	Up to: 50 pages 75 gsm bond
Faxing	
Modem Speed	Max is 33,600 bps, V.34 Half-Duplex Kbps
Supplies⁴	
Laser Cartridge Yields	up to: 4,500 ⁵ -page Black High Yield Cartridge / up to: 4,500 ⁵ -page Colour (CMY) High Yield Cartridges / up to: 1,500 ⁵ -page Black and Colour (CMYK) Cartridges
Cartridge(s) Shipping with Product	750 ⁵ -page Black Return Programme Toner Cartridge ⁵ , 500 ⁵ -page Colour (CMY) Return Programme Toner Cartridge ⁵
Paper Handling	
Included Paper Handling	100-Sheet Output Bin, Integrated Duplex, Single-Sheet Manual Feed, 250-Sheet Input
Paper Input Capacity	Up to: Standard: 250+1 pages 75 gsm bond / Maximum: 250+1 pages 75 gsm bond
Paper Output Capacity	Up to: Standard: 100 pages 75 gsm bond / Maximum: 100 pages 75 gsm bond
Media Types Supported	Hagaki Card, Paper Labels, Card Stock, Plain Paper, Envelopes, Glossy paper, Refer to the Paper & Specialty Media Guide
Media Sizes Supported	A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Hagaki Card, Letter, B5 Envelope, Statement, C5 Envelope, Executive, Universal, DL Envelope, Folio, 10 Envelope
General Information⁶	
Standard Connectivity	Gigabit Ethernet (10/100/1000), Front Hi-Speed USB port Compatible with USB 2.0 Specification (Type A), 802.11b/g/n Wireless, USB 2.0 Specification Hi-Speed Certified (Type B)
Noise Level	Operating: 50 dBA (Print) / 50 dBA (Copy) / 44 dBA (Scan)
Specified Operating Environment	Humidity: 8 to 80% Relative Humidity / Altitude: 0 - 3048 Metres (10,000 Feet) / Temperature: 10 to 32°C (50 to 90°F)
Product Guarantee	1-Onsite Repair, 3 -5 Business Days
Size / Weight	H x W x D: 344.4 x 411.2 x 394.1 mm / 19.4 kg
ENERGY STAR Typical Electricity Consumption	TEC: 0.35 kilowatt-hours per week

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹ Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

² "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³ "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴ Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. ⁵ Average continuous cartridge yield is stated number of standard pages as listed. Declared yield value in accordance with ISO/IEC 19798. ⁶ Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details.

© 2019. Lexmark. Sva prava pridržana.

Lexmark, logotip Lexmark i Unison robni su znaci tvrtke Lexmark International, Inc., registrirani u Sjedinjenim Državama i/ili drugim zemljama. AirPrint i logotip AirPrint su robni znaci tvrtke Apple, Inc. Google Cloud Print™ je robni znak tvrtke Google, LLC. Mopria® i logotipi Mopria® Logo™ i Mopria® Alliance su registrirani robni znaci i znaci usluga tvrtke Mopria Alliance, Inc. u Sjedinjenim Državama i drugim zemljama. Neovlaštena uporaba je najstrože zabranjena. Svi su drugi robni znaci imovina njihovih vlasnika. Ovaj proizvod uključuje softver koji je OpenSSL projekt razvio za uporabu u Open SSL kompletu alata (<http://www.openssl.org/>).



lexmark.rs