



MS431dn

Productivity. Reliability. Security.



MS431dn

Light, compact, and fast, the MS431dn supports output up to 40 pages per minute*. Available Extra High Yield Unison™ toner offers up to 20,000 pages of output**, while an optional 550-sheet tray supports longer print runs. A 1-GHz multi-core processor powers through big jobs, and Lexmark full-spectrum security helps protect sensitive information.

Speedy, compact printing

- ▶ Get monochrome output at up to 40 pages per minute*, with a first page as fast as 5.9 seconds.
- ▶ Tackle your printing workload with the power of a 1-GHz dual-core processor and 256 MB of memory.
- ▶ Compact dimensions of 222 mm high x 368 mm wide x 363 mm deep helps it fit almost anywhere.

Connect and control

- ▶ Connect via Gigabit Ethernet and USB.
- ▶ Two-line display lets you configure, interact with, and monitor vital system information.

Sustained output, enduring quality

- ▶ Available Extra High Yield Unison™ toner provides up to 20,000 pages** of output for more printing and less downtime.
- ▶ Optional paper tray increases total input capacity to 900 sheets to support longer print runs and enhanced media flexibility.

- ▶ Steel frame and lifetime imaging components mean long life and minimal maintenance.

Robust, built-in security

- ▶ Lexmark's full-spectrum security architecture helps keep your information safe—in the document, on the device, over the network, and everywhere in between.
- ▶ A range of embedded features harden the device against attacks.
- ▶ Standard Confidential Print feature helps ensure output security via simple PIN.

Save paper, save energy

- ▶ Automatic two-sided printing is standard.
- ▶ Built-in energy-saving modes help support ratings of EPEAT® Silver and ENERGY STAR® certified.
- ▶ The Lexmark Cartridge Collection Programme (LCCP) and Lexmark Equipment Collection Programme (LECP) minimise waste and support recycling (availability varies by country).

* Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: www.lexmark.com/ISOspeeds.

** Average continuous mono declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19752. Actual yield will vary considerably based upon many factors. See www.lexmark.com/yields for more information.

MS431dn



1 Printer with 2-line display
222 x 368 x 363 mm

2 100-Sheet multipurpose
feeder
Dimensions included as part of
base model

3 250-Sheet tray
Dimensions included as part of
base model

Standardne
 Opcije

Supports one optional 550-sheet tray.

All measurements are shown as height x width x depth. For more information about supported configurations, refer to the Printer, Option and Stand Compatibility Guide at http://www.lexmark.com/publications/furniture_safety/

Tehničke karakteristike proizvoda

Lexmark MS431dn

Ispis

Ekran	2-linijski All Points Addressable (APA) monokromatski LCD ekran
Brzina ispisa	Do: crno-bijeli: 40 stranica u minuti ¹ (A4)
Vrijeme do ispisa prve stranice	crno-bijelo: 5.9 sekundi
Rezolucija ispisa	crno-bijelo: 2400 Kvaliteta slike, 600 x 600 dpi
Memorija	Standardna: 256 MB / Maksimalna: 256 MB
Tvrdi disk	Nije dostupno
Preporučeni mjesecni ispis	800 - 8000 stranica ²
Maksimalni mjesecni ispis	Do: 80000 stranica mjesечно ³

Potrošni materijal⁴

Kapaciteti laserskih spremnika	do: Spremnik za 3.000 ⁵ stranica / do: 15.000 ⁵ stranica visoki kapacitet ulja / do: Spremnik ekstra velikog kapaciteta s crnim tonerom za 20.000 ⁵ stranica
Procijenjeni kapacitet slikovne jedinice	Do: 40000 stranica pri ispisu 3 prosječne stranice veličine letter/A4 po zadatku uz pokrivenost od ~ 5% ⁶

Spremnik/spremnići s tonerom koji dolaze s pisačem

Starter spremnik s tonerom Return Program za 3.000⁵ stranica

Rukovanje papirom

Standardni vezani uz papir	Višenamjenski ulagač od 100 listova, Integrirani dupleks, Izlazna polica za 150 listova, Ulagani kapacitet od 250 listova
Dodatne opcije vezane uz papir	550-listova ladica
Kapaciteti ulaza za papir	Do: standardno: 350 listova 75 g/m ² / maksimalno: 900 listova 75 g/m ²
Kapaciteti izlaza za papir	Do: standardno: 150 listova 75 g/m ² / maksimalno: 150 listova 75 g/m ²
Podržani tipovi medija	Papirnate naljepnice, Kartica, Običan papir, omotnice, Refer to the Paper & Specialty Media Guide
Podržane veličine medija	A6, službenoj dužnosti, 7 3/4 omotnica, 9 omotnica, JIS-B5, A4, pravni, A5, Pismo, B5 omotnica, izjava, C5 omotnica, Izvršni, univerzalan, DL omotnica, presavijen list, 10 omotnica

Osnovne karakteristike⁷

Standardni priključci	Gigabitni Ethernet (10/100/1000)
Razina buke prilikom	53 dBA (ispisivanje)
Zahtjevi vezani uz radni okoliš	Vlažnost: 8 do 80% relativne vlage / Temperatura: od 10 do 32 °C (50 do 90 °F) / Nadmorska visina: 0 - 2896 metara (9.500 stopa)
Dimenzije / Masa	V x Š x D: 222 x 368 x 363 mm / 9.3 kg
Energy Star prosječna potrošnja električne energije nsumption	TEC: 0.45 kilowatt-sat po tjednu

Sve informacije podložne su izmjenama bez prethodne obavijesti. Lexmark nije odgovoran za bilo koje greške ili propuste.

¹ Brzine ispisa i kopiranja mjerene u skladu s ISO / IEC 24734 i ISO / IEC 24735 (ESAT). Za više informacija pogledajte: www.lexmark.com/ISOspeeds. ² "Preporučena mjesecna količina stranice" je niz stranica koje korisnicima pomazu u procjeni ponuda Lexmark proizvoda temeljem prosječnog broja stranica koje korisnici planiraju ispisivati na uređaju svaki mjesec. Lexmark preporučuje da broj stranica mjesecno bude unutar navedenog raspona za optimalne performanse uređaja, na temelju čimbenika, uključujući: intervala zamjene potrošnog materijala, intervala učitavanja papira, brzine i tipične upotrebe kupaca. ³ "Maksimalni ciklus mjesecnog rada" definira se kao maksimalni broj stranica koje uređaj može isporučiti u mjesecu korištenjem višestrukih operacija. Ovaj mjerni podatak pruža usporedbu robusnosti u odnosu na druge Lexmarkove pisače i MFP-ove. ⁴ Proizvod funkcioniра samo zamjenskim uločima namijenjenima za uporabu u određenoj zemljopisnoj regiji. Više pojedinosti potražite na adresi www.lexmark.com/regions. ⁵ Prosječna standardna vrijednost prinosa stranice deklarirana u skladu s ISO / IEC 19752. ⁶ Stvarni prinos može se razlikovati ovisno o drugim čimbenicima kao što su brzina uređaja, veličina papira i orientacije hrane, pokrivanje tonera, izvor ladice, postotak ispisa samo za crno i prosječni složenost ispisa. ⁷ Pisači se prodaju pod određenim uvjetima licence / ugovora. Pogledajte www.lexmark.com/printerclicense za detalje.

© 2020 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries. Google Cloud Print is a trademark of Google, LLC. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are registered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorised use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT® is a trademark of the Green Electronics Council in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).



lexmark.hr