



Lexmark MX953se

Versatile. Simple. Sustainable.











Lexmark MX953se

With the new MX953se monochrome A3 multifunction printer, you get reassuring versatility, exceptional sustainability, and surprising simplicity from such sophisticated technology. Boost your productivity with high-quality prints - up to 55 pages per minute*. Intuitively navigate the 25 cm colour touchscreen, and save time with single-pass two-sided scanning. Effortlessly create everything your business requires, and custom configure your multifunction printer with interchangeable options tailored to your needs.

Versatile: Easy to Use

Create everything your business requires and anything you can imagine - from standard office documents to marketing brochures, booklets and posters - with broad media size support, high-volume printing, and exceptional paper handling and finishing capabilities.

Print crisp visualisations, charts and documents with deep blacks and smooth grays and a full range of media sizes so your customers can effectively communicate to co-workers, customers, and partners.

Easily incorporate your multifunction printer into your workspace with a versatile, configurable design that saves space without sacrificing performance.

Boost your productivity with our rich suite of cutting-edge software and solutions with broad capabilities including scanning paper files directly into your cloud-based storage systems and automatically translating documents into 100+languages.

Further your organisation's digital transformation with direct integration into your critical workflows and core business systems using these IoT-enabled devices.



Simple: Easy to Manage

Quickly do what you need to do using an intuitive operator panel and easy-to-follow navigation.

Easily maintain your devices with one-handed toner replacement, easy-to-reach serviceable areas, and alerts that are simple to understand.

Enjoy the peace of mind of knowing you are protected by the industry's most comprehensive security portfolio, right out of the box.

Keep your business running with exceptional reliability, industry-leading durability, and long-lasting toner and supplies.

Rest easy that every aspect of your device is made to work together seamlessly thanks to Lexmark's core technology ownership.

Sustainable: Easy to feel good about

Feel good about your purchase and help meet your own sustainability goals with our world-class practices and independent third-party certifications.

Do your part for the planet with our industry-leading use of post-consumer recycled materials and our award-winning cartridge recycling programme.


Save energy - and money - with technology that exceeds strict global standards for energy efficiency.

Minimise your impact on the environment with a company that focuses on sustainability throughout the product lifecycle from design through use, end of life and beyond.

^{*} Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: www.lexmark.com/ISOspeeds.

^{**} Fax icon shown on the operator panel when Fax Server is enabled, Fax Over IP is configured, etherFAX is configured, or an optional Analogue Modem is installed.

Lexmark MX953se



| 1 | Multifunction product with 25 cm |
|---|----------------------------------|
| | touch screen |
| | 000 500 //0 |

- 2
- 150-Sheet multipurpose feeder 3 Dimensions included as part of base model
- 4 550-Sheet tray Dimensions included as part of base model
- 5 550-Sheet Tray 163 x 587 x 649 mm
- 6 2 x 550-Sheet Tray 314 x 587 x 649 mm
- 2000-Sheet Tandem Tray A4 314 x 587 x 649 mm
- 8 Cabinet 247 x 587 x 660 mm
- 9 1500-Sheet High-Capacity Tray 290 x 342 x 545 mm

| 11 | 184 x 612 x 555 mm |
|----|--|
| 12 | 500-Sheet Staple Finisher 150 x 546 x 523 mm |
| 13 | Offset Stacker 107 x 420 x 489 mm |
| 14 | 1250-Sheet Staple 2/4 Hole Punch Finisher 995 x 575 x 610 mm |
| 15 | 2250-Sheet Booklet Staple 2/4 Hole Punch Finisher 995 x 650 x 613 mm |
| | Standard |

|) | Paper Transport Unit 143 x 412 x 466 mm | P/N 27X0420 | Memory Options 500GB Hard Disk Drive (SATA) |
|---|--|--|---|
| | Folding Paper Transport Unit 184 x 612 x 555 mm | P/N 57X0225 | Application Solutions Desktop Contactless Reader |
| 2 | 500-Sheet Staple Finisher 150 x 546 x 523 mm | 57X0235 57X0300 | Contactless Front Solutions Module (Primary Choice) Contact Authentication Device |
| 3 | Offset Stacker 107 x 420 x 489 mm | 57X0301 | Contactless Authentication Device |
| 1 | 1250-Sheet Staple 2/4 Hole Punch Finisher | 82S1203 82S1204 | IPDS License Bar Code License |
| | 995 x 575 x 610 mm | P/N | Connectivity |
| 5 | 2250-Sheet Booklet Staple 2/4 Hole Punch Finisher 995 x 650 x 613 mm | 1021231 1021294 14F0100 27X0142 | Parallel (10') Cable USB (2 Meter) Cable RS-232C Serial Interface Card Lexmark MarkNet™ N8230 |
| | Standard | 37X6146 | Fibre Ethernet Print Server Fax Card Option |
| | Optional | 57X7040 SPD0002 | English Keyboard Kit Surge Protective Device, 220-240V |
| | | P/N | Furniture |

20L8806

20L8807

Cabinet

Keyboard Shelf

| Product Specifications | Lexmark MX953se | | | | |
|--|--|--|--|--|--|
| Printing | | | | | |
| Display | Lexmark e-Task 10.1-inch (25.6 cm) colour touch screen | | | | |
| Print Speed | Up to: Black: 55 ppm ¹ (A4) | | | | |
| Time to First Page | As fast as: Black: 7.3 seconds | | | | |
| Print Resolution | Black: 1200 x 1200 dpi, 2400 IQ | | | | |
| Memory | Standard: 4 GB / Maximum: 4 GB | | | | |
| Hard Disk | Intelligent Storage Drive included; Magnetic Hard Disk available | | | | |
| Recommended Monthly Page Volume | 7,000 - 50,000 pages ² | | | | |
| Maximum Monthly Duty Cycle | Up to: 270 000 pages per month ³ | | | | |
| Copying | | | | | |
| Copy Speed | Up to: Black: 55 cpm ¹ (A4) | | | | |
| Time to First Copy | as fast as: Black: 9.1 seconds | | | | |
| Scanning | | | | | |
| Scanner Type / ADF Scan | Flatbed scanner with automatic document feeder / DADF (single pass Duplex) | | | | |
| A4/Ltr Duplex Scan Speed | Up to: Black: 200/200 Sides per minute / Colour: 200/200 Sides per minute | | | | |
| A4/Ltr Simplex Scan Speed | Up to: Black: 100/100 Sides per minute / Colour: 100/100 Sides per minute | | | | |
| ADF Paper Input Capacity | Up to: 200 pages 75 gsm bond | | | | |
| Supplies ⁴ | | | | | |
| Laser Cartridge Yields | up to: 47,700 ⁵ -page Black Cartridge | | | | |
| Imaging Unit Estimated Yield | Up to: 225,000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage | | | | |
| Cartridge(s) Shipping with Product | 5,000 ⁵ -page Black Toner Cartridge ⁵ | | | | |
| Paper Handling | | | | | |
| Included Paper Handling | 500-Sheet Output Bin, 550-Sheet Tray, 150-Sheet Multipurpose Feeder | | | | |
| Optional Paper Handling | 2,250-Sheet Booklet Staple Hole Punch Finisher, 500-Sheet Staple Offset Finisher, Folding Paper Transport Unit, 1,250-Sheet Staple Hole Punch Finisher, Offset Stacker, 1,500-Sheet High-Capacity Tray, Paper Transport Unit, 2000-Sheet Tray, Cabinet, 2 x 550-Sheet Tray, 550-Sheet Tray | | | | |
| Paper Input Capacity | Up to: Standard: 700 pages 75 gsm bond / Maximum: 4750 pages 75 gsm bond | | | | |
| Paper Output Capacity | Up to: Standard: 500 pages 75 gsm bond / Maximum: 2650 pages 75 gsm bond | | | | |
| Media Types Supported | Vinyl Labels, Labels, Card Stock, Plain Paper, Envelopes, Glossy paper, Refer to the Paper & Specialty Media Guide | | | | |
| Media Sizes Supported | Aó, Oficio, 304.8 x 483 mm, 7 3/4 Envelope, JIS-B4, 9 Envelope, JIS-B5, A3, Ledger, A4, Legal, SRA3, A5, Hagaki Card, Letter, B5 Envelope, C4 Envelope, Statement, C5 Envelope, Executive, DL Envelope, Folio, 10 Envelope | | | | |
| General Information | | | | | |
| Standard Ports | Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), 802.11a/b/g/n/ac + Apple iBeacon, USB 2.0 Specification Hi-Speed Certified (Type B) | | | | |
| Optional Network Ports / Optional Local Ports | MarkNet N8230 Fiber Ethernet Print Server / Internal 1284-B Bidirectional Parallel, Internal RS-232C serial | | | | |
| Noise Level | Operating: 51 dBA (Print) / 53 dBA (Copy) / 42 dBA (Scan) | | | | |
| Specified Operating Environment | Altitude: 0 - 2896 Metres (9,500 Feet) / Humidity: 15 to 80% Relative Humidity / Temperature: 10 to 32.2°C (50 to 90°F) | | | | |
| Product Guarantee | 1-Year Onsite Repair, Next Business Day | | | | |
| Size / Weight | H x W x D: 809 x 592 x 660 mm / 73.9 kg | | | | |
| ENERGY STAR Typical Electricity Consumption | TEC: 0.8 kilowatt-hours per week | | | | |

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹ Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

© 2024 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are registered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorised use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT® is a trademark of the Green Electronics Council in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (http://www.openssl.org/).



² "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³ "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴ Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. ⁵ Average standard page yield value declared in accordance with ISO/IEC 19752.