



Lexmark CX737adzse

All about performance and versatility





Lexmark CX737adzse

The Lexmark CX737adze colour printer is versatile for both traditional and specialized media to meet a variety of business requirements. Designed for customers who require mid-to-large workgroup colour devices, with monthly print volumes up to 20,000 pages. Unique technological approach offers exceptional print performance in off-standard printing such as greeting cards, pill pack labels, hazardous materials labelling and a whole range of narrow printing uses at speeds up to 52/50 ppm (letter/A4) * and 25 ppm (narrow).

Lexmark's new VariTherm technology

- Lexmark's new VariTherm[™] technology senses media size and adjusts heating for the media width to offer exceptional print performance on media narrower than 8.5 x 11 inches or A4.
- Particularly suited to industries such as healthcare (medicine labels, chart cards, badge media), manufacturing (paint can labels, lumber and steel tags, bar codes), and retail (signage, bottle and box labels).

Security features protect your data, your device and your network

- Security ecosystem is designed to overcome the most complex data challenges.
- Includes standard Trusted Platform Module** that stores encryption keys on separate hardware from the data, along with authentication and system integrity checks.
- Cryptographic capabilities create a unique digital fingerprint.

Easy to manage without burden on IT staff

- Our sophisticated, IoT-enabled printers are loaded with sensors that continuously monitor hundreds of data points.
- When you connect your device to Lexmark Cloud Services, you can optimize performance and uptime with additional features like predictive service and automatic supplies replenishment.

Built-in workflow solutions work for your business

- Includes standard access to Scan Centre, an easy-to-use app that simplifies routing to multiple destinations simultaneously.
- Shortcut Centre is also included, allowing you to create

personalized shortcuts for frequent copy, fax and e-mail tasks.

 Embedded solutions framework allows you to add apps that matter to your business; choose from our library or compose your own.



Keep the productivity flowing

- Maximize productivity with single-pass two-sided scanning with ultrasonic multifeed detection for fast and reliable scanning.
- The Intelligent Storage Drive (ISD) provides solid state storage with activation-ready preloaded add-on solutions.
- A large, button-free touchscreen helps users intuitively complete every task, from the basic to the complex.

Professional colour for all your print jobs

- Enjoy vibrant colour with standard advanced features like PANTONE® calibration and Lexmark Named Colour Replacement for consistent branding and professional appearance.
- Models ship with 5000-page black/colour cartridges.***
- Cartridges are also available with yields up to 28,000/ 16,200 black/colour.***

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/nondomestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

^{*} Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: www.lexmark.com/ISOspeeds.

^{**} The Trusted Platform Module (TPM) is not available in some countries.

^{***} Average continuous black or continuous composite colour (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See www.lexmark.com/yields for more information.

Lexmark CX737adzse

LCX					
				P/N 47C9700	Hardware Lexmark CX737adzse
	8	1:00		<mark>P/N</mark> 71C0W00	Supplies Lexmark CS/CX730, 735, C/ XC4342, C4352 170K Waste
			For	71C0Z10	Container Lexmark CS/CX730, 735, C/ XC4342, C/XC4352 Black 150K Imaging Unit
		2		71C0Z50	Lexmark CS/CX730, 735, C/ XC4342, C/XC4352 Colour (CMY) 150K Imaging Unit
				71C10C0	Lexmark CS/CX730, 735 Cyan Return Programme 5K Toner Cartridge
				71C10K0	Lexmark CS/CX730, 735 Black Return Programme 5K Toner Cartridge
	4			71C10M0	Lexmark CS/CX730, 735 Magenta Return Programme 5K Toner Cartridge
	5			71C10Y0	Lexmark CS/CX730, 735 Yellow Return Programme 5K Toner Cartridge
	6		5	81C0X10	Lexmark CX735 Black 28K Toner Cartridge
				81C0X20	Lexmark CX735 Cyan 16.2K Toner Cartridge
				81C0X30	Lexmark CX735 Magenta 16.2K Toner Cartridge
				81C0X40	Lexmark CX735 Yellow 16.2K Toner Cartridge
				P/N 40C2100 47C4500	Paper Handling 550-Sheet Tray Convenience Stapler
	7			4/C4300 P/N	
				27X0400	Memory Options 500+ GB Hard Disk
				P/N 57X0225	Application Solutions Desktop Contactless Reader
	Multifum ation was durat with 10 in al. (25	4		57X0225	Contactless Front Solutions
1	Multifunction product with 10-inch (25 cm) touch screen 621 x 479 x 533 mm	6	550-Sheet Tray 119 x 463 x 483 mm 4.7 x 18.23 x 19 in.	57X0300 57X0301	Module (Primary) Contact Authentication Device Contactless Authentication
2	24.44 x 18.85 x 20.9 in.	7	Adjustable Stand 521 x 653 x 625 mm	82\$1203	Device IPDS License
Z	550-Sheet tray with 100-sheet multipurpose feeder		20.5 x 25.7 x 24.6 in.	82\$1204	Bar Code License
	Dimensions included as part of base model	8	Convenience Stapler LV 82 x 109 x 121 mm	P/N 1021294	Connectivity USB (2 Meter) Cable
3	550-Sheet Tray 119 x 463 x 483 mm 4.7 x 18.23 x 19 in.		3.23 x 4.29 x 4.77 in.	27X0823	MarkNet N8370 Wireless for CS720, CS725, CX725
4	550-Sheet Tray 119 x 463 x 483 mm 4.7 x 18.23 x 19 in.		Standard	27X6410	Lexmark MarkNet N8372 802.11 a/b/g/n/ac Wireless Print Server
			Optional	SPD0001	Surge Protective Device, 110-120V
5	550-Sheet Tray 119 x 463 x 483 mm			P/N 40C2300	Furniture Adjustable Stand
	4.7 x 18.23 x 19 in.				

Product Specifications	Lexmark CX737adzse
Printing	
Display	Lexmark e-Task 10.1-inch (25.6 cm) class colour touch screen
Print Speed	Up to: Black: 52 ppm ¹ (Letter) / Colour: 52 ppm ¹ (Letter)
Time to First Page	as fast as: Black: 6.6 seconds / Colour: 6.6 seconds
Print Resolution	Black: 1200 x 1200 dpi, 4800 CQ (2400 x 600 dpi) / Colour: 4800 CQ (2400 x 600 dpi), 1200 x 1200 dpi
Memory	Standard: 2048 MB / Maximum: 2048 MB
Hard Disk	Intelligent Storage Drive included; Magnetic Hard Disk available
Recommended Monthly Page Volume	2000 - 20000 pages ²
Maximum Monthly Duty Cycle	Up to: 150000 pages per month ³
Copying	
Copy Speed	Up to: Black: 52 cpm ¹ (Letter) / Colour: 52 cpm ¹ (Letter)
Time to First Copy	as fast as: Black: 6.7 seconds / Colour: 6.8 seconds
Scanning	
Scanner Type / ADF Scan	Flatbed scanner with ADF / DADF (single pass Duplex)
A4/Ltr Duplex Scan Speed	Up to: Black: 98 / 104 sides per minute / Colour: 98 / 104 sides per minute
A4/Ltr Simplex Scan Speed	Up to: Black: 49 / 52 sides per minute / Colour: 49 / 52 sides per minute
ADF Paper Input Capacity	Up to: 100 pages 20 lb or 75 gsm bond
Faxing	
Modem Speed	ITU T.30, V.34 Half-Duplex, 33.6 Kbps
Supplies ⁴	
Laser Cartridge Yields	up to: 28,000 5 -page Black Extra High Yield Cartridge / up to: 16,200 5 -page Colour (CMY) Extra High Yield Cartridges
Imaging Unit Estimated Yield	Up to: 150000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage 6
Cartridge(s) Shipping with Product	5,000 ⁵ -page Black and Colour (CMYK) Return Programme Toner Cartridges ⁵
Paper Handling	
Included Paper Handling	100-Sheet Multipurpose Feeder, Integrated Duplex, 300-Sheet Output Bin, 550-Sheet Input
Optional Paper Handling	550-Sheet Tray
Paper Input Capacity	Up to: Standard: 650 pages 20 lb or 75 gsm bond / Maximum: 2850 pages 20 lb or 75 gsm bond
Paper Output Capacity	Up to: Standard: 300 pages 20 lb or 75 gsm bond / Maximum: 300 pages 20 lb or 75 gsm bond
Media Types Supported	Vinyl Labels, Banner Paper, Paper Labels, Card Stock, Plain Paper, Envelopes, Refer to the Paper & Specialty Media Guide
Media Sizes Supported	A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Letter, B5 Envelope, Statement, C5 Envelope, Executive, Universal, DL Envelope, Folio, 10 Envelope
General Information ⁷	
Standard Ports	Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear Hi-Speed USB port Compatible with USB 2.0 Specification (Type A), USB 2.0 Specification Hi-Speed Certified (Type B), One Internal Card Slot
Optional Network Ports	Internal MarkNet N8370 802.11b/g/n/a Wireless, NFC
Noise Level	Operating: 53 dBA (Print) / 56 dBA (Copy) / 51 dBA (Scan)
Specified Operating Environment	Humidity: 8 to 80% Relative Humidity / Temperature: 10 to 32°C (50 to 90°F) / Altitude: 0 - 2896 Meters (9,500 Feet)
Limited Warranty	See Statement of Limited Warranty: 1-Year Onsite Service, Next Business Day
Size / Weight	H x W x D: 621 x 479 x 533 mm / 39.5 kg
ENERGY STAR Typical Electricity Consumption	TEC: 0.69 kilowatt-hours per week

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹ Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds. ² "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³ "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴ Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. ⁵ Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798. ⁶ Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. ⁷ Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/nondomestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

© 2023 Lexmark. All rights reserved.

Lexmark, the Lexmark logo, Unison and VariTherm are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

PANTONE® is the property of Pantone LLC. All other trademarks are the property of their respective owners. Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries and regions. MOPRIA[®], the Mopria[®] Logo, and the Mopria AllianceTM word mark and logo are registered and/or unregistered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorized use is strictly prohibited.

