



---

## Lexmark CX963se

Versatile. Simple. Sustainable.

---



# Lexmark CX963se

With the new CX963se color A3 multifunction printer, you get reassuring versatility, exceptional sustainability, and surprising simplicity from such sophisticated technology. Boost your productivity with vivid prints — up to 55 pages per minute\*. Intuitively navigate the 10-inch (25 cm) color touchscreen, and save time with single-pass two-sided scanning. Effortlessly create everything your business requires, and custom configure your multifunction printer with interchangeable options tailored to your needs.

## Versatile: Easy to Use

**Create everything your business requires and anything you can imagine** — from standard office documents to marketing brochures, booklets and posters — with broad media size support, high-volume printing, and exceptional paper handling and finishing capabilities.

**Print vivid, colorful visualizations, charts and documents** with professional color features (including PANTONE® calibration) and a full range of media sizes so you can effectively communicate your ideas.

**Easily incorporate your multifunction printer into your workspace** with a versatile, configurable design that saves space without sacrificing performance.

**Boost your productivity** with our rich suite of cutting-edge software and solutions with broad capabilities including scanning paper files directly into your cloud-based storage systems and automatically translating documents into 100+ languages.

**Further your organization's digital transformation** with direct integration into your critical workflows and core business systems using these IoT-enabled devices.



## Simple: Easy to Manage

**Quickly do what you need to do** using an intuitive operator panel and easy-to-follow navigation.

**Easily maintain your devices** with one-handed toner replacement, easy-to-reach serviceable areas, and alerts that are simple to understand.

**Enjoy the peace of mind of knowing you are protected** by the industry's most comprehensive security portfolio, right out of the box.

**Keep your business running** with exceptional reliability, industry-leading durability, and long-lasting toner and supplies.

**Rest easy that every aspect of your device is made to work together seamlessly** thanks to Lexmark's core technology ownership.

## Sustainable: Easy to feel good about

**Feel good about your purchase and help meet your own sustainability goals** with our world-class practices and independent third-party certifications.

**Do your part for the planet** with our industry-leading use of post-consumer recycled materials and our award-winning cartridge recycling program.

**Save energy — and money** — with technology that exceeds strict global standards for energy efficiency.

**Minimize your impact on the environment** with a company that focuses on sustainability throughout the product lifecycle from design through use, end of life and beyond.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

\* Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

\*\* Fax icon shown on the operator panel when Fax Server is enabled, Fax Over IP is configured, etherFAX is configured, or an optional Analog Modem is installed.

# Lexmark CX963se



- 1 **Multifunction product with 10-inch (25 cm) touch screen**  
858 x 592 x 660 mm  
33.8 x 23.3 x 26.0 in.
- 2 **500-Sheet output bin**  
Dimensions included as part of base model
- 3 **150-Sheet multipurpose feeder**  
Dimensions included as part of base model
- 4 **550-Sheet tray**  
Dimensions included as part of base model
- 5 **550-Sheet Tray**  
163 x 587 x 649 mm  
6.4 x 23.1 x 25.6 in.
- 6 **2 x 550-Sheet Tray**  
314 x 587 x 649 mm  
12.4 x 23.1 x 25.6 in.
- 7 **2000-Sheet Tandem Tray - Letter**  
314 x 587 x 649 mm  
12.4 x 23.1 x 25.6 in.
- 8 **Cabinet**  
247 x 587 x 660 mm  
9.7 x 23.1 x 26.0 in.
- 9 **1500-Sheet High-Capacity Tray**  
290 x 342 x 545 mm  
11.4 x 13.5 x 21.4 in.

- 10 **Paper Transport Unit**  
143 x 412 x 466 mm  
5.6 x 16.2 x 18.3 in.
- 11 **Folding Paper Transport Unit**  
184 x 612 x 555 mm  
7.2 x 24.1 x 21.9 in.
- 12 **500-Sheet Staple Finisher**  
150 x 546 x 523 mm  
5.9 x 21.5 x 20.6 in.
- 13 **Offset Stacker**  
107 x 420 x 489 mm  
4.2 x 16.5 x 19.3 in.
- 14 **1250-Sheet Staple 2/3 Hole Punch Finisher**  
995 x 575 x 610 mm  
39.2 x 22.6 x 24.0 in.
- 15 **2250-Sheet Booklet Staple 2/3 Hole Punch Finisher**  
995 x 650 x 613 mm  
39.2 x 25.6 x 24.1 in.

- Standard
- Optional

P/N  
20L8300

Hardware  
Lexmark CX963se

P/N

Supplies

- 20L7500 Staple Cartridges (4-pack)
- 25A0013 Staple Cartridges (3 pack)
- 77L0H10 Lexmark MX953, CS963, CX961, 962, 963, XC9635, 9645, 9655 Black 47.7K Toner Cartridge
- 77L0H20 Lexmark CS963, CX961, 962, 963, XC9635, 9645, 9655 Cyan 46.9K Toner Cartridge
- 77L0H30 Lexmark CS963, CX961, 962, 963, XC9635, 9645, 9655 Magenta 46.9K Toner Cartridge
- 77L0H40 Lexmark CS963, CX961, 962, 963, XC9635, 9645, 9655 Yellow 46.9K Toner Cartridge
- 77L0W00 Lexmark CS963, CX950, 951, 961, 962, 963, 833, XC9525, 9535, 9635, 9645, 9655, 8355 170K Waste Container
- 77L0Z10 Lexmark MX953, CS963, CX950, 951, 961, 962, 963, 833, XC9525, 9535, 9635, 9645, 9655, 8355 Black 225K Imaging Unit
- 77L0Z50 Lexmark CS963, CX950, 951, 961, 962, 963, 833, XC9525, 9535, 9635, 9645, 9655, 8355 3-Color 250K Imaging Kit
- 77L0ZK0 Lexmark MX953, CS963, CX950, 951, 961, 962, 963, 833, XC9525, 9535, 9635, 9645, 9655, 8355 Black Return Programme 225K Imaging Unit
- 77L0ZV0 Lexmark CS963, CX950, 951, 961, 962, 963, 833, XC9525, 9535, 9635, 9645, 9655, 8355 3-Color Return Programme 250K Imaging Kit
- 77L10C0 Lexmark CS963, CX950, 951, 961, 962, 963, 833 Cyan Return Programme 12K Toner Cartridge
- 77L10K0 Lexmark MX953, CS963, CX950, 951, 961, 962, 963, 833 Black Return Programme 15K Toner Cartridge
- 77L10M0 Lexmark CS963, CX950, 951, 961, 962, 963, 833 Magenta Return Programme 12K Toner Cartridge
- 77L10Y0 Lexmark CS963, CX950, 951, 961, 962, 963, 833 Yellow Return Programme 12K Toner Cartridge
- 77L1HCO Lexmark CS963, CX961, 962, 963 Cyan Return Programme 46.9K Toner Cartridge
- 77L1HK0 Lexmark MX953, CS963, CX961, 962, 963 Black Return Programme 47.7K Toner Cartridge
- 77L1HMO Lexmark CS963, CX961, 962, 963 Magenta Return Programme 46.9K Toner Cartridge
- 77L1HY0 Lexmark CS963, CX961, 962, 963 Yellow Return Programme 46.9K Toner Cartridge
- P/N 20L8800 550-Sheet Tray
- 20L8801 2 x 550-Sheet Tray
- 20L8802 2,000-Sheet Tandem Tray – A4
- 20L8803 2,000-Sheet Tandem Tray – Letter
- 20L8804 1,500-Sheet High-Capacity Tray
- 20L8810 500-Sheet Staple Finisher
- 20L8811 Folding Paper Transport Unit
- 20L8812 1250-Sheet Staple 2/3 Hole Punch Finisher
- 20L8813 1250-Sheet Staple 2/4 Hole Punch Finisher

|         |  |
|---------|--|
| 20L8814 | 2250-Sheet Booklet Staple 2/3<br>Hole Punch Finisher |
| 20L8815 | 2250-Sheet Booklet Staple 2/4<br>Hole Punch Finisher |
| 20L8816 | Offset Stacker                                       |
| 20L8817 | Paper Transport Unit                                 |

**P/N**      **Memory Options**  
 27X0420      500GB Hard Disk Drive (SATA)

**P/N**      **Application Solutions**  
 57X0225      Desktop Contactless Reader  
 57X0235      Contactless Front Solutions  
                   Module (Primary)  
 57X0300      Contact Authentication Device  
 57X0301      Contactless Authentication  
                   Device  
 82S1203      IPDS License  
 82S1204      Bar Code License

**P/N**      **Connectivity**  
 1021231      Parallel (10') Cable  
 1021294      USB (2 Meter) Cable  
 14F0100      RS-232C Serial Interface Card  
 27X0142      Lexmark MarkNet™ N8230 Fiber  
                   Ethernet Print Server  
 37X6146      Fax Card Option  
 57X7040      English Keyboard Kit  
 SPD0001      Surge Protective Device,  
                   110-120V

**P/N**      **Furniture**  
 20L8806      Cabinet  
 20L8807      Keyboard Shelf

You can install one 550-Sheet tray.

You can install one 2x550-Sheet tray, one 2,000-Sheet tandem tray or one Cabinet, but you must also install one 550-Sheet tray above it.

You can install one 1,500-Sheet high-capacity tray, but you must install one 2x550-Sheet tray or one 2,000-Sheet tandem tray beside it.

You can install one 500-Sheet staple finisher, one Offset stacker or one Folding paper transport unit.

You can install one 1,250-Sheet staple hole punch finisher or one 2,250-Sheet booklet staple hole punch finisher, but you must also install a Paper transport unit or Folding paper transport unit, one 550-Sheet tray, and one 2x550-Sheet tray or one 2,000-Sheet tandem tray or one Cabinet.

| Product Specifications                        |   | Lexmark CX963se |
|---|---|-----------------|
| <b>Printing</b>                               |   |                 |
| Display                                       | Lexmark e-Task 10.1-inch (25.6 cm) class colour touch screen  |                 |
| Print Speed                                   | Up to: Black: 55 ppm <sup>1</sup> (Letter) / Colour: 55 ppm <sup>1</sup> (Letter)   |                 |
| Time to First Page                            | as fast as: Black: 7.1 seconds / Colour: 8.2 seconds  |                 |
| Print Resolution                              | Black: 1200 x 1200 dpi, 4800 Color Quality / Colour: 4800 Color Quality, 1200 x 1200 dpi  |                 |
| Memory  | Standard: 4 GB / Maximum: 4 GB  |                 |
| Hard Disk                                     | Intelligent Storage Drive included; Magnetic Hard Disk available  |                 |
| Recommended Monthly Page Volume               | 7,000 - 50,000 pages <sup>2</sup>   |                 |
| Maximum Monthly Duty Cycle                    | Up to: 270 000 pages per month <sup>3</sup>   |                 |
| <b>Copying</b>                                |   |                 |
| Copy Speed                                    | Up to: Black: 55 cpm <sup>1</sup> (Letter) / Colour: 55 cpm <sup>1</sup> (Letter)   |                 |
| Time to First Copy                            | as fast as: Black: 8.5 seconds / Colour: 9.5 seconds  |                 |
| <b>Scanning</b>                               |   |                 |
| Scanner Type / ADF Scan                       | Flatbed scanner with automatic document feeder / DADF (single pass Duplex)  |                 |
| A4/Ltr Duplex Scan Speed                      | Up to: Black: 240/240 sides per minute / Colour: 240/240 sides per minute   |                 |
| A4/Ltr Simplex Scan Speed                     | Up to: Black: 120/120 sides per minute / Colour: 120/120 sides per minute   |                 |
| ADF Paper Input Capacity                      | Up to: 300 pages 20 lb or 75 gsm bond   |                 |
| <b>Supplies<sup>4</sup></b>                   |   |                 |
| Laser Cartridge Yields                        | up to: 46,900 <sup>5</sup> -page Colour (CMY) Cartridges / up to: 47,700 <sup>5</sup> -page Black Cartridge   |                 |
| Imaging Unit Estimated Yield                  | Up to: 225,000 (black) and 250,000 (colour) pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage  |                 |
| Cartridge(s) Shipping with Product            | 15,000 <sup>5</sup> -page Black Toner Cartridge <sup>5</sup> , 12,000 <sup>5</sup> -page Colour (CMY) Toner Cartridges <sup>5</sup>   |                 |
| <b>Paper Handling</b>                         |   |                 |
| Included Paper Handling                       | 500-Sheet Output Bin, 550-Sheet Tray, 150-Sheet Multipurpose Feeder   |                 |
| Optional Paper Handling                       | 2,250-Sheet Booklet Staple Hole Punch Finisher, 500-Sheet Staple Offset Finisher, Folding Paper Transport Unit, 1,250-Sheet Staple Hole Punch Finisher, Offset Stacker, 1,500-Sheet High-Capacity Tray, Paper Transport Unit, 2000-Sheet Tandem Tray, Cabinet, 2 x 550-Sheet Tray, 550-Sheet Tray |                 |
| Paper Input Capacity                          | Up to: Standard: 700 pages 20 lb or 75 gsm bond / Maximum: 4750 pages 20 lb or 75 gsm bond  |                 |
| Paper Output Capacity                         | Up to: Standard: 500 pages 20 lb or 75 gsm bond / Maximum: 2650 pages 20 lb or 75 gsm bond  |                 |
| Media Types Supported                         | Vinyl Labels, Labels, Card Stock, Plain Paper, Envelopes, Glossy paper, Refer to the Paper & Specialty Media Guide  |                 |
| Media Sizes Supported                         | A6, Oficio, 12 x 18", 7 3/4 Envelope, JIS-B4, 9 Envelope, JIS-B5, A3, Ledger, A4, Legal, SRA3, A5, Hagaki Card, Letter, B5 Envelope, C4 Envelope, Statement, C5 Envelope, Executive, DL Envelope, Folio, 10 Envelope  |                 |
| <b>General Information</b>                    |   |                 |
| Standard Ports                                | Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), 802.11a/b/g/n/ac + Apple iBeacon, USB 2.0 Specification Hi-Speed Certified (Type B)   |                 |
| Optional Network Ports / Optional Local Ports | MarkNet N8230 Fiber Ethernet Print Server / Internal 1284-B Bidirectional Parallel, Internal RS-232C serial   |                 |
| Noise Level                                   | Operating: 51 dBA (Print) / 52 dBA (Copy) / 50 dBA (Scan)   |                 |
| Specified Operating Environment               | Altitude: 0 - 2896 Meters (9,500 Feet) / Humidity: 15 to 80% Relative Humidity / Temperature: 10 to 32.2°C (50 to 90°F)   |                 |
| Limited Warranty                              | See Statement of Limited Warranty: 1-Year Onsite Repair, Next Business Day  |                 |
| Size / Weight                                 | H x W x D: 858 x 592 x 660 mm / 90.1 kg   |                 |
| ENERGY STAR Typical Electricity Consumption   | TEC: 0.82 kilowatt-hours per week   |                 |

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

<sup>1</sup> Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

<sup>2</sup> "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. <sup>3</sup> "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. <sup>4</sup> Product functions only with replacement cartridges designed for use in a specific geographical region. See [www.lexmark.com/regions](http://www.lexmark.com/regions) for more details. <sup>5</sup> Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

© 2024 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are registered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorized use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT® is a trademark of the Green Electronics Council in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).



